

First Hit**End of Result Set**

L2: Entry 2 of 2

File: JPAB

Nov 14, 1979

PUB-NO: JP354145785A

DOCUMENT-IDENTIFIER: JP 54145785 A

TITLE: SILANE-MODIFIED WAX AND ITS PREPARATION

PUBN-DATE: November 14, 1979

INVENTOR-INFORMATION:

NAME

COUNTRY

INAGAKI, HAJIME

IGARASHI, TSUTOMU

TOMOSHIGE, TORU

YUZAWA, MOTOYASU

ASSIGNEE-INFORMATION:

NAME

COUNTRY

MITSUI PETROCHEM IND LTD

APPL-NO: JP53053820

APPL-DATE: May 8, 1978

INT-CL (IPC): C08F 291/00; C08F 2/00; C09D 3/82; C09J 3/14

ABSTRACT:

PURPOSE: To prepare a post-curable silane-modified wax useful for adhesives, coating additives, etc., having excellent solvent resistance, adhesive properties, etc., by the graft-copolymerization of a wax with a specific silane compound.

CONSTITUTION: (A) 100 parts by weight of a wax having an intrinsic viscosity $[\eta]$ of 0.05 ~ 0.8 (pref. olefin wax) is reacted with (B) preferably 0.5 ~ 100 parts by weight of a silane compound having an olefinic unsaturated bond-containing group and a hydrolyzable organic group. The reaction is carried out under non-extrusion molding condition in the presence of a radical initiator adding the (B) compound at a rate of, e.g. 1~10 mM/min/kg-wax. The reaction gives a graft copolymer containing 0.3 ~ 45 wt.% of grafted silane compound. Preferably the silane-modified wax has a penetration degree of 0 ~ 50 and a melt viscosity of 1 ~ 300,000 cps at 160°C.

COPYRIGHT: (C)1979,JPO&Japio